

663 0003

Material Safety Data Sheet
May be used to comply with
OSHA's Hazard Communication Standard,
29 CFR 1910.1200. Standard must be
consulted for specific requirements.

U.S. Department of Labor
Occupational Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072



IDENTITY (As Used on Label and List)
TENSIVE® CONDUCTIVE ADHESIVE GEL

Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.

Section I

Manufacturer's Name

Emergency Telephone Number

Section II – Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
NONE				

Section III – Physical/Chemical Characteristics

Boiling Point	N/A	Specific Gravity (H²O = 1)	1.0
Vapor Pressure (mm Hg.)	N/A	Melting Point	N/A
Vapor Density (AIR = 1)	N/A	Evaporation Rate (Butyl Acetate = 1)	N/A

Solubility in Water
SOLUBLE

Appearance and Odor
VISCIOUS, AMBER COLORED GEL; PERFUMED ODOR

Section IV – Fire and Explosion Hazard Data

Flash Point (Method Used) N/A	Flammable Limits N/A	LEL N/A	UEL N/A
---	--------------------------------	-------------------	-------------------

Extinguishing Media
USE EXTINGUISHING MEDIA APPROPRIATE FOR SURROUNDING FIRE.

Special Fire Fighting Procedures
NONE

Unusual Fire and Explosion Hazards
NONE

